

Lawncare

Main

More Info Manuals Brochures Safety Accessories Gallery

19" Bluebird Lawn Aerator Manufactured by Bluebird, USA.



The Bluebird Lawn Aerator provides for ease of operation, optimum results and extended unit life. At the turn of a knob, the operator can preset the height of the rear wheels thereby controlling penetration depth of the hardened-steel, cylindrical tines. Adjustments in rear wheel height can also be made to assist machine stability and manoeuvrability.

Altering the Aerator's mass when adjusting to differing soil conditions is simple. Instead of wasting time and water filling and/or emptying water tanks, two solid weights can easily be removed or added to offer optimal soil penetration and balance for easier slope aeration.

In keeping with Bluebird's philosophy of building the longest possible working life into each unit, sealed ball bearings are used to mount the semi-pneumatic wheels to the front shaft while the solid-rubber rear wheels (moulded on cast-metal) are attached to the unit with roller bearings.

The use of a protected roller chain in the secondary drive to the tine assembly and front wheel is of special interest to operators in our dusty Australian conditions, as it reduces downtime considerably and also extends unit life. The plugs removed by the Bluebird Aerators are deposited back on the lawn where they break down and become top dressing.

All Diushird aquinment is newered by a Drigge 9



SUBARU

Industrial

Power <u>Pr</u>oducts

Model Number	530
Engine Make	Briggs & Stratton
Engine	4.0hp Briggs & Stratton
Engine Features	6:1 with Spring-loading belt idler. Handle Control
Starting System	Recoil Start
Fuel Type	Petrol
Fuel Tank (L)	2.8L
Noise Level (dB @ 7m)	67db
Operation Width (mm)	19" (480mm)
Weight (kg)	131kg
Dimensions (LxWxH)	1220x736x1295mm
Dimensions Folded (LxWxH)	1020x736x710mm
Manufacturers Warranty	12 months
Engine Warranty	3 years
Operational Depth	Up to 3"





